



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- BA96 BASKET SPUN DFSMALL
- CC3 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 300 mm
- CN3 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 300 mm
- SLS3 Lincat Silverlink 600 Free-standing Floor Stand - for units W 300 mm
- HC3 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 300 mm - 0.25 kW
- HCL3 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 300 mm - 0.25 kW

PRODUCT FEATURES

- Delivering 12kg of chips per hour, perfect for cafes, pubs and restaurants
- Front mounted controls for safety
- Hinged elements to give easy access during cleaning
- Cool zone collects cooking debris & gives cleaner cooking results and saves money by prolonging the life of the oil
- Thermostatically controlled to give accurate cooking temperatures throughout cooking. Fail safe top temperature cut out ensures safe operation.
- Fully moulded 304 stainless steel tank and heavy duty nickel plated baskets for the most demanding of operations
- Plug and play for an easy installation

UK Fry perfectly crisp and fluffy chips every single time with the Silverlink 600 Electric Counter Top Fryer. Delivering 12kg of chips per hour, it's ideal for cafes, pubs and restaurants. The fryer is designed to plug in and play so you'll be serving perfect chips in no time at all. The fryer comes with an innovative deep cool zone, which collects cooking debris to prolong the life of the oil and therefore save you money. Sturdy stainless steel means it's built to last, hinged elements give easy access during cleaning, and you're in control via the accurate thermostat throughout the entire cooking process.

AIA FILE NUMBER:

ITEM NUMBER:

WEIGHTS & DIMENSIONS

Product Width	300 mm
Product Depth	600 mm
Product Height	330 mm
Product Dimensions (WxDxH) (mm)	300 Millimeter X 600 Millimeter X 330 Millimeter
Product Weight	13 kg
Product Clearance Required: Top	1,000 mm
Product Clearance Required: Back	100 mm
Product Clearance Required: Left Side	100 mm

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	40 cm
Ship Height	49.5 cm
Ship Weight	14.3 kg
Ship Method	Small Parcel (Ups Fedex Dhl)
Shipping Package Type	Pieces

PRODUCT CERTIFICATION ICONS



ENERGY SPECIFICATIONS

Primary Energy Type	Electric
Electrical Volts	230V

ADDITIONAL TECHNICAL SPECIFICATIONS

Basket Lift Type	Not Applicable
Food Production Rate	8kg chips-12mm [frozen], 12kg chips-12mm [chilled] per hour
Temperature Maximum	190 °C
Total Oil Capacity (volume)	7.5 l
Vat 1 Oil Capacity (volume)	7.5 l

bidding specifications

TECHNICAL DRAWING

