

GAS RANGE

MODEL: INF-32NR

**OPERATING
INSTRUCTIONS**

oker is designed according to the same kind products of America

nder gas as fuel and has the advantages of easy operation, safety

ns:

WTB-32-NR

6kw/h

ue:77.3 billion joules

ption:0.7NM³/H

m):600×600×600

: LPG

operation gas is cylinder gas with low-pressure regulator

n location and notes:

g the pipeline to the cylinder and the connection to see if it is in g

e safety valve is in the OFF position of the closed state, press the safe
counterclockwise by 30 degrees to make the safety valve in the slot p
bout 30-45 seconds (cycle operation).Then find the burner correspond
and use the ignition gun to ignite the normally open fire corresponding
n the thermocouple of the flameout device is heated to a certain exten
valve (under the condition that the normally open fire is not extinguished
e kindling of the burner is ignited, rotate the safety valve counterclockw
d the burner is in a normal combustion state.

ition gun does not work, please the

Cleaning and maintenance:

eaning, you must shut off the valve of wok and clean the plate below the
wel.

ne, the burners and the plates can be removed for cleaning.

Don't clean the machine by using a steam cleaner.

uct can use liquified gas and natural gas as the gas sup
nd the corresponding nozzle needs to be used for the co