

REFRIGERATOR COMPACT K220R DR G U

Product series: Compact

Item number: 151220030

The GRAM compact series offers a rare combination: they are food safe cabinets, compact in size and with excellent energy ratings for its class.

These small space storage cabinets are easy to fit in especially where space is of a premium. This makes the COMPACT series a very popular choice amongst small kitchen operators who do not require heavy duty gastronorm refrigeration. The COMPACT K220R DR G U is a REFRIGERATOR with a net internal volume of 77 ltr. The dimensions are mm.

COMPACT AND HIGHLY VERSATILE

This compact storage cabinet is easy to fit into your kitchen design, especially when space is of a premium.

HIGH STANDARD HYGIENE

The one piece inner lining with its smooth surfaces and seamless construction allows for a straight forward easy cleaning routine.

UNIFORM TEMPERATURES

Automatic defrost and a smart air distribution system ensures correct and uniform temperatures at all times preserving the taste, texture and nutritional content of your fresh goods.

FULL HEIGHT INTEGRATED HANDLE

Easy grip and easy access for cleaning.

EASY CLEANING

Rounded corners and base, seamless surfaces and removable door seal ensures cleaning routines become a quick and simple task.



SPECIFICATIONS

Product title	REFRIGERATOR	Connection load (Watt)	70
Temperature range	+1/+12°C	Energy consumption Ecodesign AEC (kWh/Year)	197
Volume, gross (ltr.)	123	Energy Efficiency Class (ISO 22041-2019)	A++
Net usable volume (ltr.)	77	Energy Efficiency Index EEI	9.92
Exterior	Stainless	Sound level – dB(A)	38.8
Interior	White Finish	Climate class	4
Dimensions W x D x H (mm)	595 x 645 x 833	Refrigerant (kg)	0.036
Weight, packed (kg)	52	CO2 equivalent (kg)	0.108
Insulation (mm)	52 mm (polyurethane)	GN – Shelf size	Shelf 483.8 x 433 mm
Refrigerant	R600a	Maximum number of shelves	9
GWP	3	Number of shelves	2
Refrigeration capacity at -10°C (Watt)	63	Equipped with	Right hand hinged reversible door with lock, 2 white shelves, bottom shelf 484.7 (W) x 300 (D) mm. Exterior: Stainless. Interior: PS lining in white
Connection	230V, 50 Hz	Door Type	Solid Door